


**SECTION A-A**

**NOTE:**

1. 'T'= THICKNESS IN SIXTEENTHS FROM 1/16" TO 1 11/16". SPECIFY WHEN ORDERING.
2. MATERIAL-ASTM A36 STEEL. STAINLESS STEEL IS AVAILABLE AS AN OPTION; SPECIFY WHEN ORDERING.
3. CARBON STEEL RINGS, GREATER THAN 1/4" THICK, ARE HOT DIP GALVANIZED PER ASTM A123. CARBON STEEL RINGS, 1/4" THICK OR LESS, ARE ZINC PLATED PER ASTM B633 TYPE II CLASS I OR HIGHER.
4. THIS PRODUCT IS CERTIFIED PER FAA ADVISORY CIRCULAR AC150/5345-42 (CURRENT REV).

FAA TYPE	NOM DIA	MMC TYPE	'OD'	'BC'	'ID'
L-867B	12"	127S	13.500	10.250	9.250
L-867D	16"	167S	17.375	14.250	12.375
L-867E	24"	247S	24.000	21.500	20.000

DWN: DOUG F.	<b>L-867 SPACERS</b>			<b>MILLERBERND</b>	622 6TH ST. SO. WINSTED, MN 55395	<b>7S</b>
DATE: 7/17/2017						
SCALE: NTS						
SHEET 1 OF 1						