



SECTION A-A
WITH PLYWOOD COVER
AND MACHINE SCREWS

FAA TYPE	NOM DIA	MMC TYPE	'OD'	'BC'	'ID'	'ODB'	'ODT'
L-868A	8"	88BSC	8.500	6.250	5.250	9.500	9.500
L-868B	12"	128BSC	12.500	10.250	9.250	13.500	13.500
L-868C	15"	158BSC	15.500	13.250	12.375	16.500	16.500

NOTE:

1. SPECIFY HEIGHT 'HT' WHEN ORDERING, 4 1/2" MINIMUM.
2. TAPPED HOLE PATTERN IN TOP FLANGE IS ALIGNED WITH CENTERLINE OF COUPLINGS.
3. 2" COUPLINGS ARE ORIENTED 180° APART. OTHER COUPLING SIZES AND/OR LOCATIONS MUST BE SPECIFIED WHEN ORDERING.
4. THREADS INSIDE THE COUPLINGS ARE PROTECTED WITH LDPE PLUGS.
5. PLYWOOD COVER IS EXTERIOR GRADE CC.
 - L-868 8" DIA: 3/4" THICK
 - L-868 12" DIA: 3/4" THICK
 - L-868 15" DIA: 1 1/4" THICK
6. A COPPER GROUND LUG IS INCLUDED.
7. CARBON STEEL SECTIONS ARE HOT DIP GALVANIZED PER ASTM A 123.
8. AVAILABLE OPTIONS, SPECIFIED WHEN ORDERING, INCLUDE:
 - DRAIN COUPLING
 - ANTI-ROTATION FINS AND/OR ANTI-UPLIFT BARS
 - STAINLESS STEEL CONSTRUCTION
 - REPLACEABLE STAINLESS STEEL THREADED INSERTS
9. THIS PRODUCT IS CERTIFIED PER FAA ADVISORY CIRCULAR AC150/5345-42 (CURRENT REV).

DWN: DOUG F.	L-868 BOTTOM SECTION W/COUPLINGS	
DATE: 7/26/2017		
SCALE: NTS	 MILLERBERND	622 6TH ST. SO. WINSTED, MN 55395
SHEET 1 OF 1		