



NOTE:

1. 24" IS THE STANDARD HEIGHT; OTHER HEIGHTS ARE AVAILABLE. 36" MAX.
2. TAPPED HOLE PATTERN IN TOP FLANGE IS ALIGNED WITH CENTERLINE OF GROMMET OPENINGS.
3. 2" GROMMET OPENINGS ARE ORIENTED 180° APART. OTHER HOLE SIZES AND/OR LOCATIONS MUST BE SPECIFIED WHEN ORDERING.
4. (2) Ø 2" GROMMETS (STD) ARE SHIPPED UNASSEMBLED WITH BASE.
- ⑤ PLYWOOD COVER IS EXTERIOR GRADE CC.
  - L-868 8" DIA: 3/4" THICK
  - L-868 12" DIA: 3/4" THICK
  - L-868 15" DIA: 1 1/4" THICK
6. A COPPER GROUND LUG IS INCLUDED.
7. CARBON STEEL BASES ARE HOT DIP GALVANIZED PER ASTM A123.
8. AVAILABLE OPTIONS, SPECIFIED WHEN ORDERING, INCLUDE:
  - DRAIN COUPLING
  - ANTI-ROTATION FINS AND/OR ANTI-UPLIFT BARS
  - STAINLESS STEEL CONSTRUCTION
  - REPLACEABLE STAINLESS STEEL THREADED INSERTS
9. THIS PRODUCT IS CERTIFIED PER FAA ADVISORY CIRCULAR AC150/5345-42 (CURRENT REV).

FAA TYPE	NOM DIA	MMC TYPE	'OD'	'BC'	'ID'	'ODB'	'LRD'
L-868A	8"	88CG	8.500	7.250	6.500	9.500	10.000
L-868B	12"	128CG	12.500	11.250	10.00	13.500	14.000
L-868C	15"	158CG	15.500	14.250	13.00	16.500	17.000

DWN: DOUG F.	L-868 LIGHT BASE WITH GROMMETS	
DATE: 7/11/2017		
SCALE: NTS	 <b>MILLERBERND</b>	622 6TH ST. SO. WINSTED, MN 55395
SHEET 1 OF 1		