



NOTE:

- 'HT' = HEIGHT TO ORDER. MINIMUM HEIGHT IS 4.0".
- PLYWOOD COVER FOR L-868 TOP SECTION IS 3/4" NOMINAL THICKNESS, GRADE CC. PLYWOOD COVER DIAMETERS:
 - L-868 8" NOM. OD: 3/4" THICK
 - L-868 12" NOM OD: 3/4" THICK
 - L-868 15" NOM OD: 1 1/4" THICK
- FINISH-HOT DIP GALVANIZED PER ASTM A123.
- CARBON STEEL SECTIONS ARE HOT DIP GALVANIZED PER ASTM A123.
- AVAILABLE OPTIONS, SPECIFIED WHEN ORDERING, INCLUDE:
 - STAINLESS STEEL CONSTRUCTION
 - REPLACEABLE STAINLESS STEEL THREADED INSERTS
- THIS PRODUCT IS CERTIFIED PER FAA ADVISORY CIRCULAR AC150/5345-42 (CURRENT REV).

FAA TYPE	NOM DIA	MMC TYPE	'ODC'	'ODF'	'BC'	'ID'
L-868A	8"	88MS	8.500	9.500	6.250	5.250
L-868B	12"	128MS	12.500	13.500	10.250	9.250
L-868C	15"	158MS	15.500	16.500	13.250	12.375

DWN: DOUG F.

DATE: 8/1/2017

SCALE: NTS

SHEET 1 OF 1

L-868 MIDDLE SECTION



MILLERBERND

622 6TH ST. SO.
WINSTED, MN
55395

8MS