



SECTION A-A

NOTE:

1. 'T'= THICKNESS IN SIXTEENTHS FROM 1/16" TO 2 3/16". SPECIFY WHEN ORDERING.
2. MATERIAL-ASTM A36 STEEL. STAINLESS STEEL IS AVAILABLE AS AN OPTION; SPECIFY WHEN ORDERING.
3. CARBON STEEL RINGS, GREATER THAN 1/4" THICK, ARE HOT DIP GALVANIZED PER ASTM A123. CARBON STEEL RINGS, 1/4" THICK OR LESS, ARE ZINC PLATED PER ASTM B633 TYPE II CLASS I OR HIGHER.
4. THIS PRODUCT IS CERTIFIED PER FAA ADVISORY CIRCULAR AC150/5345-42 (CURRENT REV).

FAA TYPE	NOM DIA	MMC TYPE	'OD'	'BC'	'ID'
L-868A	8"	88S	8.000	7.250	6.500
L-868B	12"	128S	12.000	11.250	10.000
L-868C	15"	158S	15.000	14.250	13.000

DWN: DOUG F.	L-868 SPACER RING, Ø8", Ø12" & Ø15"		 MILLERBERND	622 6TH ST. SO. WINSTED, MN 55395	8S
DATE: 8/10/2017					
SCALE: NTS					
SHEET 1 OF 1					