



SECTION A-A

NOTE:

1. 'T'= THICKNESS IN SIXTEENTHS FROM 1/16" TO 1 15/16". SPECIFY WHEN ORDERING.
2. MATERIAL-ASTM A36 STEEL. STAINLESS STEEL IS AVAILABLE AS AN OPTION; STECFY WHEN ORDERING.
3. CARBON STEEL RINGS, GREATER THAN 1/4" THICK, ARE HOT DIP GALVANIZED PER ASTM A123. CARBON STEEL RINGS, 1/4" THICK OR LESS, ARE ZINC PLATED PER ASTM B633 TYPE II CLASS I OR HIGHER.
4. THIS PRODUCT IS CERTIFIED PER FAA ADVISORY CIRCULAR AC150/5345-42 (CURRENT REV).

FAA TYPE	NOM DIA	MMC TYPE	'OD'	'BC'	'ID'
L-868A	8"	88SMB	9.000	6.250	5.250
L-868B	12"	128SMB	13.000	10.250	9.250
L-868C	15"	158SMB	16.000	13.250	12.375

DWN: DOUG F.	L-868 SPACER RING-MIDDLE & BOTTOM SECTIONS		 MILLERBERND 622 6TH ST. SO. WINSTED, MN 55395	8SMB
DATE: 8/10/2017				
SCALE: NTS				
SHEET 1 OF 1				