



SECTION A-A

FAA TYPE	NOM DIA	MMC TYPE	'IDR'	'BC'	'ID'
L-868A	8"	88SY	8.160	7.250	6.500
L-868B	12"	128SY	12.160	11.250	10.000
L-868C	15"	158SY	15.160	14.250	13.000

NOTE:

1. 'T'= THICKNESS IN SIXTEENTHS FROM 1/4" TO 1 15/16". SPECIFY WHEN ORDERING.
2. (6) 3/8-16 UNC STAINLESS STEEL HEX HEAD BOLTS AND CEC LOCK WASHERS ARE SHIPPED WITH L-868 Y SPACER RING. BOLT LENGTH IS BASED ON AND IS SUITABLE FOR THE THICKNESS OF THE Y SPACER RING ORDERED. IF Y SPACER RING IS TO BE STACKED OVER A SPACER RING, THE SPACER RING THICKNESS MUST BE ACCOUNTED FOR IN BOLT LENGTH DETERMINATION TO PROVIDE A MINIMUM OF 1/2" THREAD ENGAGEMENT.
3. MATERIAL-ASTM A36 STEEL. STAINLESS STEEL IS AVAILABLE AS AN OPTION; SPECIFY WHEN ORDERING.
4. CARBON STEEL RINGS, GREATER THAN 1/4" THICK, ARE HOT DIP GALVANIZED PER ASTM A123. CARBON STEEL RINGS, 1/4" THICK OR LESS, ARE ZINC PLATED PER ASTM B633 TYPE II CLASS I OR HIGHER.
5. THIS PRODUCT IS CERTIFIED PER FAA ADVISORY CIRCULAR AC150/5345-42 (CURRENT REV).

DWN: DOUG F.	L-868 SPACER RING WITH PAVEMENT RING			MILLERBERND	622 6TH ST. SO. WINSTED, MN 55395	8SY
DATE: 8/10/2017						
SCALE: NTS						
SHEET 1 OF 1						